



2244 W McDowell
Phoenix, AZ 85009
1-800-274-RACE
FAX: 602-340-8429
602-257-9591

HP4210R – C-6 REVERSE MAN. VALVE BODY

For over 45 years our goal has been to provide racers and enthusiasts with reliably engineered, U.S. manufactured, torque converters and drive train components for your high performance application. *Before you start your build, please take a few moments to review the important Product Safety Information and installation steps set out within this instruction manual.* If you still have questions; Hughes Performance® technical team is here to help: (1-800-274-RACE).

Important Product Safety Information

Throughout these instructions important safety information is generally preceded by one of three signal words indicating the relative risk of injury. The signal words mean:

! WARNING a hazardous situation which if not avoided could result in death or serious injury. **You CAN be Killed or Seriously Injured if you do not follow instructions.**

! CAUTION a hazardous situation which if not avoided could result in minor or moderate injury. **You CAN be moderately INJURED and also may suffer property damage if you don't follow instructions.**

! NOTICE careful attention is required to follow this installation instruction or operation but does generally not relate to personal injury. Damage to your product or other property may result if you do not follow instructions.

.....
! WARNING: Improper selection of Hughes Performance® products, failure to follow installation instructions and/or misuse increases the risk of injury or accident. For your safety and the safety of others:

- Assure the Hughes Performance® product selected is intended for your application with an additional safety margin above your expected horsepower, torque, and intended usage of product and vehicle.
- These instructions are not intended to address all risks related to modification of your vehicle or use. Remember: *you are the builder and*

chief safety engineer for your modified vehicle. Consult and follow all OEM warnings and operating limitations.

(For Calif. Residents-Prop. 65):

! WARNING

This product contains chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

(for more information on Prop. 65 see www.P65Warnings.ca.gov/product)

HP4210R – C-6 REVERSE MAN. VALVE BODY

1. Clearance direct clutch pack .045 to .060. Use a late C6 band with an “E” type lever and “R” or “H” code servo. “R” code servo is preferred.
2. Adjust the band to 72 in/lb. then turn out 1 1/2 turns.
3. Install the correct filter to match your pan. Be sure to reinstall the long filter bolt in the hole it came from.
4. Install valve body as is. Be sure to engage the manual valve in the shift linkage. Torque bolts to 12 ft/lb.

! WARNING: Use protective eyewear and gloves. If dusty, use face mask, wet and wipe clean working surfaces. Transmission fluids and cleaning products are highly flammable! Avoid open flame, welding sparks, smoking, or other sources of ignition. Flexplate, torque converter, and transmission assembly involves heavy parts and pinch points. Use support jacks and review installation steps before attempting.

! WARNING: Cooler fittings should never be plugged. If a cooler is not used, connect lines together with a loop of hard line or appropriate flexible hose that is compatible with automatic transmission fluid and that carries a minimum 500 PSI rating.

